

LCD Fitting Checklist for PANTS

SET UP

- Wear undergarments and the shoes you'll wear with the finished pants.
- Put the test pants on inside out (seams out). Let them settle.
- Stand naturally, walk a few steps.
- Take photos (natural light): front, side, back.

NON-NEGOTIABLES

- Tightness first is the only exception.
- Otherwise: **Length, then Circumference, then Depth.**
- **One change at a time:** pin, baste, re-check.

L: LENGTH (position first)

- **Crotch position first.** Do not judge wrinkles until they're in place. Pin side seams to ensure the crotch stays where you want it.
- Check landmarks: waistline, fullest hip level, knee level (if visible).
- Fix length, then re-check.

C: CIRCUMFERENCE (breathing room)

- Movement test: sit, walk, step up, bend.
- **Need more room:** let out **darts first**, then seams evenly.
- **Need less room:** take in **seams first**, then fine-tune with darts.
- Try not to modify the center front and back as they are already on a bias.
- Re-check grain and side seam placement.

D: DEPTH (front, back, crotch shape)

- Only after L + C are set.
- Redistribute fabric where needed (seat, front thigh, crotch curve).
- Pin one change, let settle, reassess.

COMMON CLUES (PANTS)

- **Crotch wrinkles or pulling:** check crotch position (Length) before anything else.
- **Horizontal strain at hip, thigh, or seat:** need more circumference.
- **Diagonal drag lines into crotch:** depth redistribution and shaping.
- **Baggy under seat but tight elsewhere:** depth issue, take a dart at center back about 2-3" above the fullest part of the hips (tapering to nothing at the side seams).

FINISH

- Baste changes. Try on again. Re-check in LCD order.